



The New Maximus™ - Faster and better than ever!

The new and improved Maximus™ time clock delivers a straightforward user interface and provides employees the ability to perform fast clock in and clock out transactions.

Accu-Time Systems reengineered the Maximus to outperform its predecessor with a faster processor, greater memory capacity, and a full-color 3.5" screen. The new Maximus is ideal for small businesses or large enterprises that require frequent employee punches. With its back-lit screen and extremely durable keypad, this time clock makes it easier for employees to see and perform accurate employee time tracking transactions..

Maximus™ features include:

- Eight programmable function keys
- Remote upgradeability
- Biometric option eliminates costly buddy-punching
- Optional power-over-Ethernet module
- Optional GSM modem
- Optional WIFI 802.11 a,b,g,n; WPA2
- DHCP & static IP

To learn more about ATS and Maximus, visit www.accu-time.com or call -1 860.870.5000



Maximus™ Terminal Specifications

Display	<ul style="list-style-type: none">• 3.5" non-touch transmissive color LCD
Keypad	<ul style="list-style-type: none">• 20-key tactile 4x5 matrix<ul style="list-style-type: none">» Numeric keypad 0-9» Eight software-defined function keys» Keys, Clear/Enter keys• Customizable overlay with your brand on the terminal
Processor	<ul style="list-style-type: none">• IMX28 - 454MHZ
Memory	<ul style="list-style-type: none">• 512MB NAND FLASH
Mass Storage	<ul style="list-style-type: none">• 8GB eMMC for CM/Recovery OS Programming
Ethernet	<ul style="list-style-type: none">• Standard 10/100 BASE-T Ethernet• DHCP & Static IP• USB - 2 USB 2.0 Type A Connectors
Application Software	<ul style="list-style-type: none">• OS - Linux• SDK Java SDK, Java 8, Python
Platform OS	<ul style="list-style-type: none">• ATS AccuCollect• ATS Universal Command Set (UCS)
Power	<ul style="list-style-type: none">• 5W Average, 12.95W Maximum• Optional IEEE 802.3af-compliant Power over Ethernet (PoE)
Environment	<ul style="list-style-type: none">• Operation Temperature: 0° to 50°C (32° to +122°F)• Storage Temperature: -20° to 80°C (-4° to +176°F)
Dimensions	<ul style="list-style-type: none">• 21.33 cm x 22.22 cm x 9.91 cm (8.4" x 8.75" x 3.9")
Enclosure	<ul style="list-style-type: none">• Die-cast aluminum housing hinged to key-lockable base
Certifications	<ul style="list-style-type: none">• CE Mark, FCC Part 15 Class A
Accessories	<ul style="list-style-type: none">• Biometric readers• Digital Persona• Optical and Capacitive Suprema, Lumidigm• Smartcard readers – contactless (HID® Prox, Mifare™, iClass®)• Optional external reader - Wiegand compatible & USB• WIFI 802.11 a,b,g,n; WPA2

ACCU-TIME SYSTEMS INC.

THE AMERICAS

Corporate Headquarters

20-B International Drive

Windsor, CT 06095

TEL: (860) 870-5000

FAX: (860) 872-1511

Toll Free: (800) 355-4648

sales@accu-time.com

www.accu-time.com

EMEA & APAC

United Kingdom

TEL: +44 (0) 1202 606068

All Other Locations

TEL: +44 (0) 2920 885599

