

timecom®
a time collection solution

PeoplePoint™ Plus



Flexible Clock-in Options

- Proximity Card Reader
- Fingerprint Biometric Reader
- Keypad

PEOPLEPOINT™ PLUS: VERSITILE WORKFORCE MANAGEMENT, POWERED BY TIMECOM

The PeoplePoint Plus time clock is engineered for versatility and reliability across industries, delivering near real-time, accurate workforce data with seamless integration to TimeCom. Featuring a large 7" touchscreen and a powerful processor, it supports multiple authentication options including biometric, proximity card, keypad, and swipe card, customizable to fit any operational need. This integration allows organizations to streamline labor management, enforce compliance, reduce time fraud, and empower employees with intuitive self-service. The PeoplePoint Plus transforms workforce management into a strategic advantage, just like stride80, offering flexibility and control in diverse, high-demand environments.

PEOPLEPOINT PLUS FEATURES INCLUDE:

- 7" Easy-to-Use Touch Display
- Flexible Clock-in Options
- Quick Employee Verification
- Durable, Robust Design
- Ideal for High-Volume, Fast-Paced Industrial Settings.

Flexible Clock-in Options



Proximity Card Reader



Keypad



PeoplePoint™ Plus Time Clock Specifications

User Interface	7" TFT Capacitive Touch, 800 x 480 Resolution 20-key tactile, 4x5 matrix <ul style="list-style-type: none">· Numeric keypad 0-9· Eight software definable function keys· Clear/Enter keys Customizable overlay allows for unique graphic options
CPU	Freescale iMX6 up to 1GHz (Single Core)
Memory	1GB DDR3 RAM 512MB NAND FLASH
Mass Storage	Non-removable eMMC 8GB, of which 2.0GB are user available
Programming	Linux OS standard. Java™/Python Web services - HTML capable Software Development Kit (SDK)
Application Software	ATS AccuCollect - Configurable punch workflow management including job transfers, attestations, and more
Communications	Standard 10/100 BASE-T Ethernet Internal USB port Optional Wi-Fi with WPA support Optional internal 3G cellular modem
Enclosure	PC/ABS
Certifications	CE Mark, FCC Part 15 Class A
Dimensions	H 26.67cm x W 22.86cm x D 10.16cm H 10.5" x W 9" x D 4"
Power	12 VDC (nominal) 1A, 12W maximum under normal operation Optional uninterruptible power supply Optional IEEE 802.3af/compliant POE
Environment	Operation Temperature: 0° to 50°C (32° to +122°F) Storage Temperature: -20° to 80°C (-4° to +176°F)
Accessories	Biometric readers – 1:1 and 1:n Integrated visible or infrared barcode readers Integrated magnetic stripe readers Contactless smartcard readers (HID® Prox, Mifare™, iClass®, Marin) External readers - Wiegand compatible Dry contact low voltage relay modules dual Form C Uninterruptible power supply

ACCU-TIME SYSTEMS INC.

THE AMERICAS

Corporate Headquarters
20-B International Drive
Windsor, CT 06095
TEL: (860) 870-5000
FAX: (860) 872-1511
Toll Free: (800) 355-4648
sales@accu-time.com
www.accu-time.com

EMEA & APAC

United Kingdom
TEL: +44 (0) 1202 606068

All Other Locations

TEL: +44 (0) 2920 885599

Empower Your Workforce Time Tracking with Purpose-Built Precision